

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 September 2003 (04.09.2003)


PCT

(10) International Publication Number
WO 03/072354 A1

- (51) International Patent Classification⁷: **B32B 7/12**, 9/00, 33/00, C09J 7/02
- (21) International Application Number: PCT/US03/04507
- (22) International Filing Date: 19 February 2003 (19.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/358,352 22 February 2002 (22.02.2002) US
- (71) Applicant (for all designated States except US): **MAGNUM MAGNETICS CORPORATION** [US/US]; Route 3, Box 347, Marietta, OH 45750 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SCHNEIDER, Jon, B.** [US/US]; Route 3, Box 329, Marietta, OH 45750 (US). **MEDLEY, Keith** [US/US]; 115 Skyvue Circle, Marietta, GA 45750 (US).
- (74) Agent: **BOLAND, Thomas, R.**; Vorys, Sater, Seymour and Pease, LLP, 1828 L Street, N.W., Suite 1111, Washington, DC 20036-5104 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:**
— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: MAGNETIC LABEL STOCK MATERIAL



(57) Abstract: A magnetic label stock material (100) for applying magnetic labels (108) to a substrate includes a flexible translucent release tape (102) having magnetic labels (108) adhered thereto with a pressure sensitive adhesive. The magnetic labels (108) are spaced along said tape (102) with light-transmissive gaps therebetween, and the magnetic labels (108) extend substantially to the edges (106) of said tape (102) in order to support and reinforce the edges (106) of the tape (102) and prevent damage to the tape (102) in handling and use.

WO 03/072354 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.